AXAF COMMAND ACTION PROCEDURE

CAP #:775
DATE: 10 January 2002

ORIGINATOR: Shanil Virani
COMMANDS CHECKED BY: R. Buehler, Y. Butt
Time of CAP Execution (GMT): 2002:011:21:15

DESCRIPTION/RATIONALE

Command ACIS to execute a CTI (I-array) measurement.

RESTRICTIONS/WARNINGS/NOTES/SCHEDULE REQT:

EPHIN rates are 1/3 of the SCS107 trigger levels.
It is assumed that the JAN1202 SCS107 replan load is running on the spacecraft.
RADMON will be enabled by this CAP if necessary.
SCS107 will be enabled by this CAP if necessary.
The TLM FMT will be changed to FMT 2 by this CAP if necessary.
The OBSID will be set to 62853 in this CAP.
It is assumed the load will execute an ACIS StopScience command at 2002:012:03:30:00.
This load uses an SCS (1A_CTI00_137) which bundles together 6 ACIS commands.

STEP	INSTRUCTIONS (Command/Script)	RESPONSE (TLM Verifier)
1	Verify that EPHIN rates are less than 1/3 of the SCS107 trigger levels.	
2	Verify that the JAN12 SCS107 REPLAN load is loaded and active on the spacecraft.	
3	Ensure that the SIM is at HRC-S.	
4	Set the TLM FMT to 2, if necessary.	
5	Enable RADMON if necessary, issue command OORMPEN	CORADMEN=ENAB OR RADMON=ENAB
6	Enable SCS107 if necessary	
7	Set OBSID=62853	
8	Uplink Load: 1A_CTI00_137.CLD	E1940CB
9	Enable and Activate SCS 137	WSVIDALLDN (command ID = 1541) WSPOW0CF3F (command ID = 359) RS_0000001 (command ID = 66) RH_0000001 (command ID = 68) WT00216014 (command ID = 2034) XTZ0000005 (command ID = 58)
10	ACIS confirms normal science run.	
11	Clear and Disable 137	

Approved:

Subsystem Engineer:
FOT Manager:
SOT Lead:

Flight Director:
Program Manager: