AXAF COMMAND ACTION PROCEDURE

CAP #:851
DATE: 30 May 2003

ORIGINATOR: Joe DePasquale
COMMANDS CHECKED BY: P. Plucinsky
Time of CAP Execution (GMT): 2003:150:22:00

DESCRIPTION/RATIONALE

Command ACIS to execute a CTI (I-array) measurement.

RESTRICTIONS/WARNINGS/NOTES/SCHEDULE REQT:

EPHIN rates are 1/3 of the SCS107 trigger levels.
It is assumed that the MAY3103 SCS107 replan load is running on the spacecraft.
RADMON will be enabled by this CAP if necessary.
SCS107 will be enabled by this CAP if necessary.
The TLM FMT will be changed to FMT 2 by this CAP if necessary.
The OBSID will be set to 62847 in this CAP.
It is assumed the load will execute an ACIS StopScience command at 2003:151:13:00.
This load uses an SCS (1A_CTI01_138) which bundles together 6 ACIS commands.

STEP	INSTRUCTIONS (Command/Script)	RESPONSE (TLM Verifier)
1	Verify that EPHIN rates are less than 1/3 of the SCS107 trigger levels.	
2	Verify that the MAY3103 SCS107 REPLAN load is loaded and active on the spacecraft.	
3	Ensure that the SIM is at HRC-S.	
4	Set the TLM FMT to 2, if necessary.	
5	Enable RADMON if necessary, issue command OORMPEN	CORADMEN=ENAB OR RADMON=ENAB
6	Enable SCS107 if necessary	
7	Set OBSID=62847	
8	Uplink Load: 1A_CTI01_138.CLD	96BD4D3
9	Enable and Activate SCS 138	WSVIDALLDN (command ID = 1541) WSPOW0CF3F (command ID = 359) WT00216024 (command ID = 4536) XTZ0000005 (command ID = 58) RS_0000001 (command ID = 66) RH_0000001 (command ID = 68)
10	ACIS confirms normal science run.	
11	Clear and Disable 138	

Approved:

Subsystem Engineer:
FOT Manager:
SOT Lead:

Flight Director:
Program Manager: